

"Express Mail" mailing label number EH862489285US

Date of Deposit Jan. 26, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" services under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Typed Name of Person Mailing Paper or Fee: Betty Hinkle

Signature: Betty Hinkle

**PATENT APPLICATION
DOCKET NO. 10002193-1**

METHOD AND DEVICE FOR LOCATING A PERIPHERAL

INVENTOR(S):

Larry A. Copp
Matt Howell

09771158 012601

09771158 012601

METHOD AND DEVICE FOR LOCATING A PERIPHERAL

FIELD OF THE INVENTION

This invention relates generally to computer network topology determination, and more particularly to locating a peripheral on a computer network.

BACKGROUND OF THE INVENTION

Printing a document from a client computer to a printer on a computer network is typically done through a print queue (sometimes called "printer queue"). For example, MICROSOFT WINDOWS (TM) and other similar operating systems provide print queues to facilitate printing. A print queue on a network is typically shared by several client computers, to provide more economical printing capacity while providing a mechanism to accommodate print jobs that would otherwise conflict by temporally overlapping each other. A print queue is typically provided on a print server, which is one of the computers on the network. Because print queues are so prevalent, application programs (e.g., word processors, spreadsheets, browsers or draw/paint programs) typically send print jobs to a print queue and not the actual printer directly. In fact, when a print queue is utilized, application programs and users need not know -- in fact, often do not know -- a printer's address.

This is not the case for other types of peripherals. For example, a computer typically utilizes a scanner without an intermediary like a print queue. This raises a challenge when a multi-function peripheral (MFP) is deployed on a network. A multi-function peripheral is one that has two or more peripheral capabilities. Examples of multi-function peripherals are devices that are printers in combination with one or more of a scanner, copier, and facsimile.

Multi-function printers pose a device discovery problem. To utilize the device in its non-printer capacity, a client computer must discover the address of the device. However, the device, as a printer, presents itself to the client computer anonymously through a print queue. Attempts to solve this problem have been less than fully successful. One attempted solution

is a two-stage discovery process. In the first stage, the client computer contacts the print queue and determines the type of the printer device (e.g., make and model). In the second stage, the client computer searches for devices of the same type and guesses which of the possible numerous printer devices of that type is the one. This attempted solution suffers from a number of problems. First, it is fraught with ambiguity and produces unreliable results. Second, the searching increases network traffic levels.

SUMMARY OF THE INVENTION

In one respect, the invention is a method for informing a client of a peripheral address by way of a peripheral server. The method comprises the steps of receiving a first message at a peripheral server, wherein the message contains an address of the client; generating a second message containing the peripheral address; and sending the second message to the address of the client. In one embodiment, the peripheral is a printer, the peripheral server is a print queue, and the first message is a print job containing a PML object, such as UI_SELECT_OPTION. (As used herein, the term "print job" refers to information sent to a printer.) The method optionally comprises the step of spooling the print job to the printer. In some embodiments, the second message is a UDP (user datagram protocol) datagram, which has a built-in source field.

In another respect, the invention is a method for a client to discover a peripheral address by way of a peripheral server. The method comprises sending a first message to the peripheral server, wherein the first message contains an address of the client; and receiving at the client a second message containing the peripheral address. This method is typically (but not necessarily) performed at the client, whereas the preceding method is typically (but not necessarily) performed at or near the peripheral and/or the peripheral server.

In yet another respect, the invention is an apparatus. The apparatus comprises a client computer, a peripheral server and a peripheral. The peripheral server is connected to both the client computer and the peripheral. The peripheral server receives a first message from the client computer. The first message contains an address of the client computer. The

1 peripheral receives the first message and notifies the client computer of the peripheral's
2 address. In one embodiment, the peripheral directly notifies the client computer of the
3 peripheral's address. In another embodiment, the apparatus also comprises an interface,
4 which is connected between the peripheral server and the peripheral, and the interface
5 generates a message to the client computer. The message notifies the client computer of the
6 peripheral's effective address. The peripheral server may be a printer queue, and the
7 peripheral may be a multi-function peripheral.

8
9 In comparison to known prior art, certain embodiments of the invention are capable of
10 achieving certain advantages, including some or all of the following: (1) reliably discovering
11 the network address of a peripheral; and (2) eliminating network traffic associated with less
12 reliable discovery techniques. Those skilled in the art will appreciate these and other
13 advantages and benefits of various embodiments of the invention upon reading the following
14 detailed description of a preferred embodiment with reference to the below-listed drawings.

15 16 BRIEF DESCRIPTION OF THE DRAWINGS

17
18 Figure 1 is a block diagram of a client computer, peripheral server and peripheral;

19 Figure 2 is a block diagram of a client computer, peripheral server, interface and
20 peripheral; and

21 Figure 3 is a flowchart of a method according to an embodiment of the invention.

22 23 DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

24
25 Figure 1 is a block diagram of a system 100 comprising a client computer 120, a
26 peripheral server 140 and a peripheral 160, all connected on a network 180. The client
27 computer 120 may be any type of computer but is typically a personal computer, such as the
28 type that runs the Microsoft WINDOWS (TM) operating system. The peripheral 160 is
29 typically a multi-function peripheral (MFP) with printing capability, and the peripheral server
30 140 is typically a print server that includes a print queue. The client computer 120, peripheral
31 server 140 and peripheral 160 are each connected to the network 180.

1
2 In normal printing operation, a print job is typically transferred via the network 180
3 from the client computer 120 to the print queue in the peripheral server 140. The print queue
4 in the peripheral server 140 then transfers the print job via the network 180 to the peripheral
5 160. This two step process is necessary because only the peripheral server 140 is directly
6 visible to the client computer 120. When the client computer 120 must communicate directly
7 with the peripheral 160, such as when the peripheral 160 is used in a non-printing (e.g.,
8 scanning) capacity, then the client computer 120 sends a command to the peripheral server
9 140, telling the peripheral server 140 to instruct the peripheral 160 to inform the client
10 computer 120 of the network address of the peripheral 160. The command from the client
11 computer 120 to the peripheral 140 preferably includes the network address of the client
12 computer 120. The instruction from the peripheral 140 to the peripheral 160 forwards this
13 network address. The command is preferably guised as a print job; that is, the command is
14 preferably embedded in a print job that does not cause any output. When the peripheral 160
15 receives the network address of the client computer 120, then the peripheral 160 can send a
16 message to the client computer 120, informing the client computer 120 of the peripheral's
17 (160) address. Details of this method are explained below with reference to Figure 3.

18
19 The system 100 is appropriate when the peripheral 160 itself has a capability to
20 interface with and communicate on the network 180. When the peripheral 160 lacks this
21 capability, an interface 150 is utilized, as shown in the system 200 illustrated in Figure 2. The
22 interface 150 is a network host for the peripheral 160. Contemporary examples of the
23 interface 150 include the HEWLETT-PACKARD (TM) model 170X and 300X JET DIRECT
24 BOXES (TM).

25
26 Figure 3 is a flowchart of a method 300 according to an embodiment of the invention.
27 The method 300 is operable with the system 200 (Figure 2), which includes the interface 150.
28 Those skilled in the art can readily adapt the method 300 for use with the system 100.

29
30 The method 300 sends (310) a special print job to a print queue. The print queue
31 receives the special print job. The special print job is one in which is embedded a command

1 for the printer to set a predetermined variable to be a global address of the of the client
2 computer 120. The special print job contains both the command and the address value.
3 Preferably, the special print job does not contain any printable matter and therefore does not
4 produce any printed output. In the embodiment detailed below, the predetermined variable is
5 a PML (peripheral management language) object, preferably UI_SELECT_OPTION. PML is
6 a protocol for communicating with directly connected (e.g., parallel or USB (universal serial
7 bus) port) devices. PML is similar to SNMP (simple network management protocol), which
8 is used for network connected devices instead. Note that the peripheral 160 in Figure 2 is
9 connected through a direct connection port, rather than a network connection port; thus, the
10 interface 150 is necessary to host the peripheral 160 on the network 180.

11
12 The print queue spools (320) the print job to the destination printer, just as it would
13 with any print job. The printer then parses (330) the print job, as it would any print job.
14 However, when this special print job is parsed (330), the command is found. The printer then
15 executes (340) the command, setting the PML object to be the supplied computer address.
16 After execution of the command, the printer sends (350) a trap request to the interface,
17 prompting the interface to parse (360) the PML object and to send (370) a message to the
18 specified computer address. The client computer at that address receives the message. In one
19 embodiment, the message is a UDP datagram. The computer receives the message and reads
20 (380) it in order to determine the source of the message. In the case of a UDP datagram, the
21 source address is embedded in the message, as a matter of protocol. In other forms, the
22 source address could be included in the body of the message, if necessary. After completion
23 of the method 300, the computer 120 knows the network address of the peripheral 160.

24
25 If the peripheral 160 has a direct network connection and ability to communicate on
26 the network 180 directly, then the method 300 can be simplified. In particular, the parsing,
27 executing, sending and parsing steps 330-360 can be simplified. These steps can be replaced
28 with a simple step of directly executing the command to form a message to send to the
29 computer address.

30

1 What has been described and illustrated herein is a preferred embodiment of the
2 invention along with some of its variations. The terms, descriptions and figures used herein
3 are set forth by way of illustration only and are not meant as limitations. Those skilled in the
4 art will recognize that many variations are possible within the spirit and scope of the
5 invention, which is intended to be defined by the following claims -- and their equivalents --
6 in which all terms are meant in their broadest reasonable sense unless otherwise indicated.

7

8 What is claimed is:

9

09771158-012601